

GREEN GLUE COMPOUND

HIGH EFFICIENCY DAMPING COMPOUND



Product Name	Green Glue Noiseproofing Compound
Description	A latex water based viscoelastic damping compound in quart sized caulking tubes or five gallon pails.
Application	Applied between layers of drywall or wood for damping walls, ceilings, floors, and other places. Increases STC, OITC, and IIC ratings in common construction assemblies.
Features and Benefits	<ul style="list-style-type: none">• Significant gains when installed in proper assemblies within minimal cost.• Mold, bacteria, fungi, and water resistant.• Qualifies for up to 10 LEED points.• Can be installed directly under any type of flooring including ceramic tile, stone, hardwood, laminate, vinyl, VCT, and carpet.• Protects ceramic, porcelain, and stone from substrate cracks.• Made entirely in the USA.
Coverage	16 square feet per tube or 365 square feet per pail at standard coverage
Application Temp	40°F-90°F
VOC	Meets low VOC standards
Odor	Mild and temporary
Working Time	About 20 minutes
Cure Time	7 days
Viscosity	Light paste (65,000 cps)
Other Ratings	ASTM E-84 for flame spread, ASTM D-3273 for mold resistance, ASTM E-90 for airborne noise, ASTM E-492 for impact noise.

IsoStore

ADDRESS

4013 E Barber Dr
Boise ID 83716

TELEPHONE AND FAX

877.866.6473
208.369.4650

WEB

IsoStore.com
info@IsoStore.com

The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested applications may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications.