



## CLBV.R26312 Wall and Partition Facings and Accessories

[Page Bottom](#)

---

### Wall and Partition Facings and Accessories

[See General Information for Wall and Partition Facings and Accessories](#)

#### SAINT-GOBAIN PERFORMANCE PLASTICS CORP

R26312

1 SEALANTS PARK  
GRANVILLE, NY 12832 USA

Type Green Glue "Noiseproofing Compound" for use in Design Nos. [U301](#), [U302](#), [U305](#), [U309](#), [U311](#), [U314](#), [U320](#), [U326](#), [U329](#), [U330](#), [U331](#), [U332](#), [U334](#), [U336](#), [U337](#), [U338](#), [U339](#), [U340](#), [U341](#), [U342](#), [U344](#), [U347](#), [U351](#), [U354](#), [U355](#), [U356](#), [U357](#), [U358](#), [U360](#), [U364](#), [U366](#), [U379](#), [U411](#), [U417](#), [U418](#), [U420](#), [U421](#), [U425](#), [U434](#), [U439](#), [U440](#), [U442](#), [U449](#), [U450](#), [U451](#), [U453](#), [U455](#), [U460](#), [U465](#), [U466](#), [U467](#), [U473](#), [U475](#), [U485](#), [U487](#), [U493](#), [U494](#), [V417](#), [V419](#), [V420](#), [V421](#), [V432](#), [V434](#), [V450](#), [V469](#), and [V496](#).

#### Single Layer Systems:

Noiseproofing compound applied to back of additional sheet of Gypsum Board at an application rate of 0.118 lbs/ft<sup>2</sup> (two 28 oz. tubes per 4 ft x 8 ft piece of Gypsum Board). Additional layer secured to studs through base layer with fasteners equal to the length of base layer plus the additional thickness of the new face layer.

#### Multiple Layer Systems:

Noiseproofing compound applied to back of the face layer of Gypsum Board at an application rate of 0.118 lbs/ft<sup>2</sup> (two 28 oz. tubes per 4 ft x 8 ft piece of Gypsum Board). Fastening requirements per design guidelines.

[Last Updated](#) on 2010-10-01

---

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".