

# GG ACOUSTICAL SEALANT

## FLEXIBLE LATEX BASED ACOUSTICAL SEALANT



<b>Product Name</b>	Green Glue Noiseproofing Sealant
<b>Description</b>	Water based, non-toxic, nearly zero VOC flexible acoustical sealant in quart sized caulking tubes.
<b>Application</b>	Used to seal the perimeter of walls, ceilings, and floors in sound isolation rated assemblies, as well as other gaps around doors, windows, plumbing, and electrical. Rated for interior use only.
<b>Features and Benefits</b>	<ul style="list-style-type: none"><li>• Low cost per ounce compared to basic latex caulks.</li><li>• Remains flexible with minimal shrinkage.</li><li>• Paint and drywall mud can be applied over the sealant.</li><li>• Freeze and thaw stable.</li><li>• Protects ceramic, porcelain, and stone from substrate cracks.</li><li>• Made entirely in the USA.</li></ul>
<b>Coverage</b>	40-80 linear feet per tube
<b>Application Temp</b>	40°F-90°F
<b>VOC</b>	Meets low VOC standards
<b>Odor</b>	Mild and temporary
<b>Solid Content</b>	70% +/- 5%
<b>Dry Time</b>	48 hours, ready to mud or paint after 24 hours
<b>Viscosity</b>	Light paste (1,370,000-1,450,000cps)
<b>Other Ratings</b>	ASTM E-84 for flame spread, ASTM D-3273 for mold resistance, ASTM E-90 for airborne noise.

### IsoStore

#### ADDRESS

4013 E Barber Dr  
Boise ID 83716

#### TELEPHONE AND FAX

877.866.6473  
208.369.4650

#### WEB

IsoStore.com  
info@IsoStore.com

The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested applications may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications.