

GG ACOUSTICAL SEALANT



FLEXIBLE LATEX BASED ACOUSTICAL SEALANT

Product Name	Green Glue Noiseproofing Sealant
Description	Water based, non-toxic, nearly zero VOC flexible acoustical sealant in quart sized caulking tubes.
Application	Used to seal the perimeter of walls, ceilings, and floors in sound isolation rated assemblies, as well as other gaps around doors, windows, plumbing, and electrical. Rated for interior use only.
Features and Benefits	<ul style="list-style-type: none">• Low cost per ounce compared to basic latex caulks.• Remains flexible with minimal shrinkage.• Paint and drywall mud can be applied over the sealant.• Freeze and thaw stable.• Protects ceramic, porcelain, and stone from substrate cracks.• Made entirely in the USA.
Coverage	40-80 linear feet per tube
Application Temp	40°F-90°F
VOC	Meets low VOC standards
Odor	Mild and temporary
Solid Content	70% +/- 5%
Dry Time	48 hours, ready to mud or paint after 24 hours
Viscosity	Light paste (1,370,000-1,450,000cps)
Other Ratings	ASTM E-84 for flame spread, ASTM D-3273 for mold resistance, ASTM E-90 for airborne noise.

IsoStore

TELEPHONE
877.866.6473

WEB
IsoStore.com
info@IsoStore.com

The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested applications may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications.