

TOTALMASS 2 LB

MASS LOADED VINYL (MLV) BARRIER



Product Name	TotalMass 2 LB MLV Barrier
Description	A thin, solid, and flexible material distributed in rolls. The smooth solid surface blocks airborne noise transfer in mid to high frequencies.
Application	Used to resolved common resonance issues in walls, ceilings, and floors for increasing isolation in STC ratings. As well as adding mass to many different surfaces including pipes, duct, fencing, doors, and windows.
Features and Benefits	<ul style="list-style-type: none">• Significant mass within 1/4" thickness.• Sound tested to show it resolves resonance issues found in common assemblies.• Easy to cut with a razor knife.• Supports grommets for hanging installation.• Made entirely in the USA.
Dimensions	4' x 15' (60 square feet)
Thickness	1/4"
Weight	125 pounds
Color	Black
Tensile Strength	500 psi
STC Rating	STC 31 (as standalone material only)
Fire Rating	Standard roll meets UL94-HF-1 1 hour requirement in vertical installation. UL 1 hour for horizontal installation available on request.

Standalone ASTM E-90 Results

Hz	125	250	500	1000	2000	4000
TL	16	22	26	32	35	40
STC	31					

IsoStore

ADDRESS

4013 E Barber Dr
Boise ID 83716

TELEPHONE AND FAX

877.866.6473
208.369.4650

WEB

IsoStore.com
info@IsoStore.com

The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested applications may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications.